



US007592528B2

(12) **United States Patent**  
**Lyles et al.**

(10) **Patent No.:** **US 7,592,528 B2**  
(45) **Date of Patent:** **Sep. 22, 2009**

(54) **STRINGED MUSICAL INSTRUMENT USING  
SPRING TENSION**

FOREIGN PATENT DOCUMENTS

JP 2005173515 6/2005

(75) Inventors: **Cosmos Lyles**, 101 3<sup>rd</sup> Ave., New York,  
NY (US) 10003; **Paul Dowd**, Bronxville,  
NY (US)

(Continued)

(73) Assignee: **Cosmos Lyles**, New York, NY (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 315 days.

OTHER PUBLICATIONS

Peters, Randall D., "Physics of the Zero-Length Spring of  
Geoscience," printed from website <http://physics.mercer.edu/earthwaves/zero.html>, 4 pages.

(Continued)

(21) Appl. No.: **11/724,724**

*Primary Examiner*—Jeffrey Donels  
*Assistant Examiner*—Robert W Horn

(22) Filed: **Mar. 15, 2007**

(74) *Attorney, Agent, or Firm*—Knobbe, Martens, Olson &  
Bear LLP

(65) **Prior Publication Data**

US 2007/0214935 A1 Sep. 20, 2007

**Related U.S. Application Data**

(60) Provisional application No. 60/880,230, filed on Jan.  
11, 2007, provisional application No. 60/858,555,  
filed on Nov. 10, 2006, provisional application No.  
60/830,323, filed on Jul. 12, 2006, provisional appli-  
cation No. 60/782,602, filed on Mar. 15, 2006.

(51) **Int. Cl.**  
**G10D 3/12** (2006.01)

(52) **U.S. Cl.** ..... **84/297 R; 84/454**

(58) **Field of Classification Search** ..... **84/297 R,**  
**84/454**

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**


16,995 A \* 4/1857 Randle ..... 84/297 R

(Continued)

(57) **ABSTRACT**

A stringed musical instrument employs springs to apply ten-  
sion to corresponding musical strings. Each spring is chosen  
and configured for its ability to impart a string tension gen-  
erally matched to the appropriate tension of the string at  
perfect tune. Preferably, the spring is selected and arranged so  
that the tension in the string maintains at or near perfect tune  
even as the string elongates or contracts over time. In one  
embodiment, once a string is placed in appropriate tune, a  
mechanical visual indicator is set. As such, if tune of the string  
changes due to string elongation or contraction, the change is  
reflected by misalignment of the mechanical visual indicator  
even if the change cannot be aurally detected. Perfect tune can  
be reestablished by realigning the indicator. In another  
embodiment, a force modulating member is interposed  
between a spring and its corresponding musical string. The  
force modulating member is adapted so that the tension actu-  
ally applied to the string by the spring is not linearly related to  
the force exerted by the spring as the spring changes in length.

**30 Claims, 24 Drawing Sheets**



## U.S. PATENT DOCUMENTS

644,987	A *	3/1900	Lyon	84/264	5,173,565	A	12/1992	Gunn	
936,624	A *	10/1909	Hale	84/297 R	5,277,373	A	1/1994	Morton	
1,113,390	A *	10/1914	Wenzel-Schmidt	84/455	5,284,396	A	2/1994	Masumura et al.	
1,416,568	A *	5/1922	Mazzocco	84/297 R	5,293,804	A	3/1994	Myers	
1,626,753	A	5/1927	Pecina et al.		5,323,680	A	6/1994	Miller et al.	
1,684,057	A *	9/1928	Fisher	84/297 R	5,343,793	A	9/1994	Pattie	
2,070,916	A *	2/1937	Peate	84/297 R	5,359,144	A	10/1994	Benson	
2,130,248	A *	9/1938	Peate	84/297 R	5,377,926	A	1/1995	Min	
2,262,179	A	11/1941	Hammond		5,390,579	A *	2/1995	Burgon	84/454
2,453,572	A *	11/1948	Ferrier	84/297 R	5,413,019	A	5/1995	Blanda, Jr.	
2,514,835	A *	7/1950	Bredice	84/297 R	5,477,765	A	12/1995	Dietzman	
2,736,226	A *	2/1956	McBride	84/315	5,637,820	A	6/1997	Wittman	
2,741,146	A	4/1956	Fender		5,734,117	A	3/1998	Tanzella	
2,873,640	A	2/1959	Kunz		5,756,913	A	5/1998	Gilmore	
2,973,682	A *	3/1961	Fender	84/312 P	5,824,929	A	10/1998	Freeland et al.	
3,136,198	A	6/1964	Smith et al.		5,859,378	A	1/1999	Freeland et al.	
3,437,001	A	4/1969	Kraft		5,886,270	A	3/1999	Wynn	
3,575,078	A *	4/1971	Currier	84/173	RE36,484	E	1/2000	Turner	
3,580,525	A	5/1971	Dopner		6,034,311	A	3/2000	Fisher, IV	
3,583,272	A *	6/1971	Eurich	84/267	6,084,166	A	7/2000	Lee	
3,584,807	A	6/1971	Smith		6,283,397	B1	9/2001	Chen	
3,667,336	A *	6/1972	Itzler et al.	84/454	6,384,311	B1 *	5/2002	Cota	84/739
3,688,631	A	9/1972	Jackson		6,420,639	B1	7/2002	Sherlock	
3,780,612	A	12/1973	Robinson		6,437,226	B2	8/2002	Oudshoorn et al.	
3,924,820	A	12/1975	Kovar, et al.		6,723,904	B1	4/2004	Dolan et al.	
4,120,462	A	10/1978	Raasch et al.		6,825,406	B2	11/2004	Thidell	
4,129,154	A	12/1978	Bennelli		7,235,729	B2 *	6/2007	Minakuchi	84/298
4,130,045	A	12/1978	Walker		7,479,592	B1 *	1/2009	Slavik	84/313
4,137,812	A	2/1979	Franzmann		7,534,950	B2	5/2009	Lyles	
4,138,919	A	2/1979	Miller		7,541,528	B2	6/2009	Lyles	
4,161,903	A	7/1979	Sokol		7,554,023	B2 *	6/2009	Tyler	84/313
4,170,161	A	10/1979	Kaftan		2003/0094087	A1	5/2003	Gregory	
4,234,133	A	11/1980	Enneking		2003/0226441	A1 *	12/2003	Barney	84/297 S
4,348,934	A	9/1982	Ogata		2006/0117930	A1	6/2006	Folmar et al.	
4,375,180	A	3/1983	Scholz		2007/0006712	A1	1/2007	Lyles	
4,426,907	A *	1/1984	Scholz	84/454	2007/0012161	A1	1/2007	Lyles	
4,623,101	A	11/1986	Cacak		2007/0214931	A1 *	9/2007	Lyles	84/267
4,656,915	A	4/1987	Osuga		2007/0289429	A1 *	12/2007	Tyler	84/297 R
4,704,935	A	11/1987	Franklin		2008/0196571	A1	8/2008	Lyles	
4,760,622	A	8/1988	Rohrman						
4,762,046	A *	8/1988	Aspri et al.	84/294					
4,856,404	A	8/1989	Hughes, Sr.						
4,876,794	A *	10/1989	Myers	30/252					
4,882,967	A	11/1989	Rose						
4,909,126	A	3/1990	Skinn et al.						
4,955,275	A	9/1990	Gunn						
5,040,741	A	8/1991	Brown						
5,080,295	A	1/1992	Hongo et al.						
5,095,797	A *	3/1992	Zacaroli	84/455					
5,097,737	A	3/1992	Uhrig						

## FOREIGN PATENT DOCUMENTS

WO	WO00/38172	11/1999
WO	WO2007/008785	1/2007
WO	WO2007/106600	9/2007

## OTHER PUBLICATIONS

Schmidt-Jones, Catherine "Tuning Systems" Version 1.14: Dec. 8, 2006 printed from website <http://cnx.org/content/m11639/latest>, pp. 1-13.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5






FIG. 6




FIG. 6A




FIG. 7




FIG. 8




FIG. 9





FIG. 10








FIG. 12



*FIG. 13*

*FIG. 14*




FIG. 15




FIG. 16




FIG. 17




FIG. 18






FIG. 19










FIG. 22



1

## STRINGED MUSICAL INSTRUMENT USING SPRING TENSION

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application is based on and claims the benefit of U.S. Provisional Application Nos. 60/782,602, which was filed on Mar. 15, 2006, 60/830,323, which was filed on Jul. 12, 2006, 60/858,555, which was filed on Nov. 10, 2006, and 60/880,230, which was filed on Jan. 11, 2007. The entirety of each of these priority applications is hereby incorporated by reference. This application does not claim priority to copending U.S. application Ser. No. 11/484,467, which was filed on Jul. 11, 2006; however, such application is also hereby incorporated by reference in its entirety. It is contemplated that embodiments described herein may employ aspects discussed in the above-referenced applications, and vice-versa.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates to stringed musical instruments.

#### 2. Description of the Related Art

Stringed musical instruments create music when strings of the instrument vibrate at wave frequencies corresponding to desired musical notes. Such strings typically are held at a specified tension, and the musical tone emitted by the string is a function of the vibration frequency, length, tension, material and density of the string. In order to maintain the instrument in appropriate tune, these parameters must be maintained. Typically, musical strings go out of tune because of variation in string tension. Such tension changes commonly occur when, for example, the string slackens over time. Tension can also change due to atmospheric conditions such as temperature, humidity, and the like.

Tuning a stringed instrument is a process that can range from inconvenient to laborious. For example, tuning a piano typically is a very involved process that may take an hour or more. Tuning a guitar is not as complex; however, it is inconvenient and can interfere with play and/or performance.

### SUMMARY OF THE INVENTION

Accordingly, there is a need in the art for a method and apparatus for mounting strings of a stringed musical instrument so that the instrument is more likely to maintain its correct tune, slower to go out of tune, easier and faster to place in tune, and so that retuning or adjusting the tune of the strings is easily and simply accomplished. There is also a need for a string instrument that will automatically adjust for string length changes without going out of tune.

In accordance with one embodiment, a stringed musical instrument is provided comprising a musical string having first and second ends, a first receiver adapted to receive the first end and hold the first end in an adjustably fixed position, and a string mounting system adapted to receive the second end. The string mounting system comprises a spring assembly configured to apply a tension to the second end of the string so as to hold the string at a perfect tune tension. The string mounting system is adapted so that as the second end of the musical string moves longitudinally over time due to string elongation or contraction, the string tension remains within a desired range defined about the perfect tune tension.

In another embodiment, the desired range is within about 90% of the perfect tune tension. In yet another embodiment,

2

the string mounting system is adapted so that the spring maintains the string tension within the desired range when the second end moves longitudinally less than about 5% of the total string length. In some embodiments, the perfect tune tension is between about 5 pounds and 200 pounds.

In one embodiment, the desired range is within about 98% of the perfect tune tension. In other embodiments, the desired range is within about 99% or 99.5% of the perfect tune tension.

In some embodiments, the spring assembly comprises a single spring. In other embodiment, the spring assembly comprises a plurality of springs. In other embodiments, the spring assembly comprises a first spring and a second spring, the first spring adapted to support a greater magnitude of tension in the string than the second spring. The second spring is connected to the string through the mechanical interface so that a mechanical advantage or disadvantage of the second spring relative to the spring can be adjusted.

In further embodiments, the mechanical interface comprises a force modulating member that pivots as the second end of the string moves longitudinally, and the force modulating member is adapted to pivot within a range of about 10 degrees of rotation. In other embodiments, wherein the mechanical interface comprises a stop configured to prevent rotation in a rotational direction beyond a defined position. In still further embodiments, the mechanical interface comprises a sensor adapted to detect when the stop is engaged to prevent rotation and to generate a signal upon detection of such engagement.

In a still further embodiment, the stringed musical instrument additionally comprises a roller bridge disposed forwardly of the mechanical interface. The roller bridge comprises a roller and an axle, the roller being adapted to support the string and rotate about the axle, wherein a ratio of a diameter of the roller to a diameter of the axle is greater than about 20.

In accordance with another embodiment, the present invention provides a stringed musical instrument comprising a musical string, a spring, and a mechanical interface interposed between the string and the spring. The mechanical interface is adapted to communicate force from the spring to the string so that the spring provides substantially all of the tension in the musical string. The mechanical interface also is adapted to modify the force exerted by the spring so that a magnitude of tension in the musical string differs from a magnitude of force exerted by the spring.

In another such embodiment, the mechanical interface is configured so that a percent change in the force exerted by the spring corresponds to a percent change in the tension in the string, and the magnitude of the percent change in the tension in the string is less than the magnitude of the percent change in the force exerted by the spring. In some embodiments, the mechanical interface is adapted so that the magnitude of the change in tension applied to the string is not linearly related to the corresponding magnitude of the change in force exerted by the spring.

In further embodiments, the mechanical interface comprises a cam which can comprise a string receiver. In some such embodiments, the mechanical interface connects to the spring and the string so that the spring force acts with a mechanical advantage or disadvantage relative to the string. In some embodiments, the mechanical interface is configured so that as the magnitude of spring force increases, the mechanical advantage of the spring with relation to the string decreases. In some embodiments, the string receiver has a constant radius; in others, it has a varying cam radius.

3

In accordance with yet another embodiment of the present invention, a stringed musical instrument is provided comprising a musical string and a string mounting system comprising a spring assembly having a spring. A force from the spring assembly is communicated to the string so that the spring assembly provides substantially all of the tension in the musical string. Also, the string mounting system is adapted to condition the force exerted by the spring along a changing moment arm so that a change in the magnitude of force exerted by the spring results in a change in magnitude of tension applied by the spring assembly to the string that is less than the change in magnitude of force exerted by the spring.

In some embodiments, the string mounting system comprises a mechanical interface interposed between the spring and the string, and wherein the mechanical interface conditions the spring force relative to the string tension. In one such embodiment, the mechanical interface comprises a spiral-tracked conical pulley, and the musical string is supported in the track.

In accordance with yet another embodiment of the present invention, a stringed musical instrument is provided comprising a musical string and a string mounting system. The string mounting system comprises a string mount, a spring assembly having a spring, and a mechanical interface between the string mount and the spring assembly. The interface is adapted so that the spring assembly provides substantially all of the tension in the musical string. The spring is a constant force spring comprising a rolled, pre-stressed ribbon adapted to exert a force that varies less than 1% over a maximum elongation of the musical string.

In some embodiments, the mechanical interface comprises a moment arm disposed operatively between the spring and the string. The moment arm can be adjusted to tune the mechanical advantage or disadvantage provided to the spring relative to the string. In other embodiments, the constant force spring is chosen to exert a substantially constant force substantially equal to a perfect-tune tension of the musical string.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows an embodiment of a guitar employing a string mounting system depicted schematically and having aspects described herein.

FIG. 2 shows an embodiment of a guitar employing an embodiment of a string mounting system having aspects of the present invention.

FIG. 3 is a close up view of the guitar of FIG. 2 taken along lines 3-3, and showing portions of the string mounting system partially cutaway.

FIG. 3A is a close up view of a stop member in a position relative to a corresponding tube and spring connector when a corresponding string has just been placed in correct tune.

FIG. 3B shows the arrangement of FIG. 3A after the stop member has been moved to align the stop tune indicator with the tube reference indicator.

FIG. 4 is a side view of the portion of the guitar shown in FIG. 3.

FIG. 5 is a close up perspective view of another embodiment of a guitar with a string mounting system having aspects in accordance with the present invention.

FIG. 6 is a schematic side view of a string tensioner used in accordance with the embodiment illustrated in FIG. 5.

FIG. 6A is a diagram schematically representing certain relationships of the embodiment illustrated in FIG. 6.

FIG. 7 is a perspective view of the string tensioner of FIG. 6.

4

FIG. 8 is another perspective view of the string tensioner of FIG. 6.

FIG. 9 is a perspective view of the string tensioner of FIG. 6 but showing a shuttle 250 of the string tensioner disposed in a different position.

FIG. 10 is a perspective view showing a plurality of string tensioners arranged into the string mounting system of a guitar.

FIG. 11 is a rear perspective view of the string tensioners of FIG. 10.

FIG. 12 is a perspective view of a back side of the guitar of FIG. 5 showing a portion of the string tensioner system disposed in a cavity formed in the guitar body.

FIG. 13 is a graph depicting the change in spring force as the arm of the spring tensioner of FIG. 6 moves counter clockwise.

FIG. 14 is a graph depicting the change in effective lever arm of the spring as the arm of the spring tensioner of FIG. 6 moves counter clockwise.

FIG. 15 is a graph depicting the change in effective string tension resulting from the effects shown in FIGS. 13 and 14 as the arm of the spring tensioner moves counter clockwise.

FIG. 16 is a perspective view of another embodiment of a guitar employing an embodiment of a string tensioning system having aspects of the present invention.

FIG. 17 is a top view of the guitar of FIG. 16.

FIG. 18 is a side view of yet another embodiment of a string tensioner having aspects in accordance with the present invention.

FIG. 19 is a top view of another embodiment of a string mounting system employing tensioners as in FIG. 18.

FIG. 20 is a schematic view of another embodiment of a string mounting system having aspects in accordance with the present invention.

FIG. 21 is a schematic view of yet another embodiment of a string mounting system having aspects in accordance with the present invention.

FIG. 22 is a schematic view of still another embodiment of a string mounting system having aspects in accordance with the present invention.

FIG. 23A is a side view of yet another embodiment of a string tensioner having aspects in accordance with the present invention.

FIG. 23B is a side view of the string tensioner of FIG. 23A showing the spring force modulating member portion in a different rotational position.

### DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The following description presents embodiments illustrating aspects of the present invention. It is to be understood that various types of musical instruments can be constructed using aspects and principles as described herein, and embodiments are not to be limited to the illustrated and/or specifically-discussed examples, but may selectively employ various aspects and/or principles disclosed in this application. For example, for ease of reference, embodiments are disclosed and depicted herein in the context of a six-string guitar. However, principles as discussed herein can be applied to other stringed musical instruments such as, for example, violins, harps, and pianos.

With initial reference to FIG. 1, a guitar 30 is illustrated. The guitar 30 comprises a body 32, an elongate neck 34, and a head 36. A first end 38 of the neck 34 is attached to the body 32 and a second end 40 of the neck 34 is attached to the head 36. A fretboard 42 having a plurality of frets 44 is disposed on

5

the neck 34, and a nut 46 is arranged generally at the point when the neck 34 joins with the head 36. Six tuning knobs 48A-F are disposed on the head 36. Six musical strings 50A-F are also provided, each having first and second ends 52, 54. The first end 52 of each string 50 is attached to an axle 56 of a corresponding tuning knob 48, and at least part of the string 50 is wrapped about the tuning knob axle 56. Each string 50 is drawn from the tuning knob 48 over the nut 46, and is suspended between the nut 46 and a string mounting system 60 disposed on a front face 62 of the body 32. The second end 54 of each musical string 50 is attached to the string mounting system 60.

In a conventional guitar, the string mounting system 60 comprises a stop having a plurality of slots generally corresponding to the strings. Preferably, the second end of each string includes a ball or the like that is configured to fit behind the slot so that the string ball is prevented from moving forwardly past the slot. A bridge usually is provided in front of the stop. By turning the tuning knobs a user tightens the strings so that they are suspended between the bridge and the nut. This suspended portion of the string 50, when vibrated, generates a musical note and can be defined as a playing zone 63 of the strings. The tuning knobs 48 are used to adjust string tension until the desired string tune is attained.

The illustrated embodiment is an electric guitar, and additionally provides a plurality of pickups 64, which include sensors 66 adapted to sense the vibration of the strings 50 and to generate a signal that can be communicated to an amplifier. Controllers 68 such as for volume control and the like are also depicted on the illustrated guitar 30.

In the embodiment illustrated in FIG. 1, the string mounting system 60 is depicted schematically. Applicants anticipate that string mounting systems having various structures can be employed with such a guitar 30.

With reference next to FIG. 2, an embodiment of a guitar 30 having features substantially similar to the guitar depicted in FIG. 1 is illustrated. However, the illustrated guitar additionally includes an embodiment of a string mounting system 70 that includes springs 71 to tension the musical strings 50.

With more particular reference to FIGS. 3-4, the illustrated string mounting system 70 includes a frame 72 that is mounted onto the guitar body 32. The frame 72 grasps both the front face 62 and a back 74 of the guitar body 32. The illustrated system 70 comprises a bridge 76 having string tracks or saddles 78 adapted to accommodate corresponding strings 50.

With specific reference to FIG. 3, the illustrated string mounting system 70 includes a plurality of spring assemblies 80A-F, each assembly dedicated to secure a corresponding musical string 50A-F. Each spring assembly 80 includes a spring holder or tube 82 that generally encloses a spring 71. Each elongate spring 71 has a first end 82 and a second end 86. A base connector 88 is provided along the length of the spring tube 82, and the first end 84 of the spring 71 is attached to the base connector 88. An elongate spring connector 90 also has a first end 92, a second end 94, and an elongate body 95 therebetween. The second end 94 of the spring connector 90 preferably comprises an aperture 96 or the like to facilitate connecting to the second end 86 of the spring 71, preferably within the tube 82. The first end 92 of the spring connector 90 preferably comprises a ball, disc or other mechanical interface structure 98 having an expanded width relative to the body 95.

A plurality of string holders 100 are provided, each having two receivers 102, 104. A first receiver 192 is adapted to engage the ball 98 on the first end 94 of the spring connector 90. A second receiver 104 of each string holder 100 is adapted

6

to receive and secure a ball connector 108 on the second end 54 of the respective musical string 50. As such, the string holder 100 connects a musical string 50 to the spring connector 90, and the spring connector 90 connects the string holder 100 to the spring 71. Thus, each spring 71 is mechanically connected to a corresponding musical string 50 so that spring tension is communicated to the string 50. In this embodiment, the connection is achieved by a mechanical interface that includes the spring connector 90 and string holder 100. It is to be understood that, in other embodiments, mechanical interfaces having different structural characteristics may be used to connect the string 50 to the spring 71.

An elongate stop 110 is provided on and attached to each elongate spring connector 90. Preferably, each stop 110 includes a ridge 112 sized and adapted to engage an end 114 of the corresponding spring tube 82 when the corresponding string 50 is slack or unconnected. As such, the spring 71 is kept in a pre-stressed condition, even when the corresponding musical string 50 is slack or not attached. Since the spring is already pre-stressed when the string 50 is connected when stringing the instrument, it is relatively quickly and easily tightened to string tension corresponding to correct tune. Thus, quick initial tuning is facilitated by this structure.

Preferably, each spring 71 is chosen and arranged so that its pre-stressed condition is close to, but not less than, the nominal tension associated with the corresponding string's proper tuning. For instance, if the string 50 is properly tuned at a tension of 17 lb., the pre-stressed condition of the spring 71 preferably is greater than about 15 lbs., and may be almost 17 lbs. Preferably, the pre-stressed condition is within about 25% of the proper tuning tension. More preferably, the pre-stressed condition is within about 10% of the proper tuning tension. Even more preferably, the pre-stressed condition is within about 5% of the proper tuning tension.

Properly pre-stressing the spring 71 may be accomplished in various ways. For example, in the illustrated embodiment, the first end 84 of each spring 71 is attached to its corresponding base connector 88 arranged in the tube 82. The base connector 88 is placed along the length of the tube 82 so that when the first end 84 of the spring 71 is attached to the base connector 88 and the second end 86 of the spring 71 is attached to the spring connector 90, the spring 71 is maintained at its appropriate pre-stressed tension. In a preferred embodiment, the position of each base connector 88 is chosen so that the corresponding spring 71 is placed in a desired pre-stressed tension when connected. It is to be understood, however, that other factors may also be varied. For example, in addition to or instead of varying the position of the base connector 88, varying characteristics of the spring, such as using a spring having a special chosen spring rate, may customize the spring arrangement for specific corresponding strings.

In the illustrated embodiment, the base connectors 88B, 88C, 88E comprise screws driven through the tubes 82 at desired locations. In additional embodiments, the base connectors may have different structures. For example, base connector 88F is a rod extending through the tube 82. In other embodiments, such base connector structures may be attached, welded, clipped or the like at specified locations along the tube. Preferably, connectors 116 are also provided at a distal end 118 of each tube 82 and, as with base connector 88A, may function as the base connector.

With the spring 71 in a pre-stressed state, initial tuning of the guitar 30 is relatively quick and easy. To string the guitar 30 illustrated in FIGS. 2-4, the first end 52 of each string 50A-F is appropriately attached to its corresponding tuning knob 58A-F and the second end 54 is attached to a corre-

sponding string holder **100**. The tuning knob **48** is then turned to take up the slack in the string **50** so that the spring **71** is engaged. Further turning of the tuning knob **48** with the spring **71** engaged increases tension applied to the string **50** by the spring **71**. Preferably, the spring **71** is chosen to have a rate (increase in lbs. of tension applied per inch of elongation) adapted so that it will take only one to a few turns of the tuning knob **48** to achieve a musical string tension corresponding to proper string tune.

In a preferred embodiment, a spring **71** having a rate of about 20 lb./in is employed. However, it is to be understood that a wide range of spring rates can be employed. For example, a spring **71** having a rate of about 40 lb./in could be used, and would enable use of shorter spring tubes **82**. Conversely, a spring having a rate of 1-5 lb./in could also be used. With such a spring, elongation of the corresponding musical string, which happens naturally, will have little effect on tune of the string, and thus the instrument will stay in or close to tune despite string elongation.

In the illustrated embodiment, the spring connector bodies **95** and the attached stops **110** are matingly threaded so that each stop **110** is movable over its corresponding elongate spring connector **90**. Further, a tune indicator line **120** preferably is provided circumferentially around a portion of each stop **110**; a tune indicator reference line **122** is also provided on each tube **82**. A view hole **124** preferably is formed through each tube **82** so that a portion of the stop **110** within the tube **82** is visible through the view hole **124**. Preferably, the reference line **122** on the tube is provided adjacent the view hole **124**.

With specific reference to FIGS. 3A and 3B, to achieve a visually-indicated tune of the illustrated guitar, the strings **50** are first installed and preferably tuned by a conventional method. The stops **110** are not involved in the initial tuning procedure, and the stop reference line **120** and tube reference line **122** likely will not be aligned, as depicted on FIG. 3A. Once the strings **50** are tuned, each stop **110** is moved along its corresponding spring connector **90** so that the stop tune indicator **120** is aligned with the reference indicator **122** on the corresponding tube **82** as depicted in FIG. 3B. Such alignment establishes a mechanical and visual indicator of a perfectly-in-tune condition. The position of the stop **110** on the spring connector **90** does not affect tension applied to the string **50**, so moving the stop **110** establishes a reference point without affecting string tension.

Musical strings tend to stretch during play due to environmental changes or other factors. In the past, a musician would have to periodically stop play to check or retune his instrument. Such tuning required plucking or otherwise sounding the string **50**, and then using a tuner, ear, or other method to verify and/or adjust the tune. Certain electronics-based products including sensors may also be used to determine tune. Also, electromechanical devices employing motor-driven tuning knobs controlled by electronic controllers based on sensor input can also be employed.

In the illustrated embodiment, change in the elongation of the strings **50** will be mechanically indicated by the stop and tube reference indicators **120**, **122** going out of alignment. This can be visually checked by the user, and even visually corrected by adjusting the tuning knob **48** until the indicators **120**, **122** are again aligned. With the indicators **120**, **122** returned to alignment, the instrument is again in perfect tune since the spring **71** is again stretched to the displacement (and corresponding tension) corresponding to perfect tune, which measurement was established when the instrument was initially tuned. As such, tune can be checked and corrected without ever sounding the string **50**. Also, elongation of a

string **50** can be identified and corrections made even before there is an audible effect on the string's tune.

With continued reference to FIGS. 3, 3A and 3B, the illustrated embodiment shows alternatives for indicator line configurations. For example, in tubes **82**A, B and C, reference indicators **122** are printed directly on the tubes. In tubes **82** D, E, and F, a dark coating **128** is deposited on the tubes around the view hole **124**, and the reference indicator lines **122** are printed on the dark coating **128** so as to provide increased contrast.

Other embodiments can use various structures and methods to increase visibility of the indicator lines **120**, **122**. For example, in one embodiment, the indicator lines are made using a phosphor or other material that will enable the lines to glow and/or more readily reflect light. As such, the alignment of the indicator lines **120**, **122** can be easily observed even by a musician performing in a darkened venue. In still another embodiment a light source, such as an LED or laser, is provided on the mounting system, such as in or around the frame **72**, in or on the spring tubes **82**, or elsewhere, so as to directly or indirectly illuminate the indicator lines **120**, **122** and/or provide a back light to aid viewing of the indicator lines. Still further lighting structures and methods, such as fiber optics and the like, can also be employed.

For example, the indicator **122** may include an aperture, and the indicator **120** may comprise a precisely-focused light, such as from a laser or fiber optic. When the indicators **120**, **122** are appropriately aligned, the light is visible through the aperture. In another embodiment, the aperture includes a light-diffusing material that will glow when light impinges thereon. In still another embodiment, indicator **120** includes the aperture and indicator **122** includes the light.

In yet another embodiment, rather than providing a view aperture **124** in the spring tubes **82**, the reference tune is determined by aligning the stop reference line **120** with the end **114** of the spring tube **82**. In still other embodiments, a reference for aligning with the stop **120** can be provided on the body of the guitar, on the frame, or in any other suitable location.

In still another embodiment, a first photodetector is disposed immediately adjacent a first side of the reference line **122** and a second photodetector is disposed immediately adjacent a second side of the reference line **122**. A laser or other precisely-focused light source is provided at the stop reference line **120**. The photodetectors are adapted so that they do not see the light source when the stop is properly aligned. However, if the string elongates or contracts sufficient to move the stop **100**, the light source will be detected by one of the photodetectors.

Preferably, each photodetector is adapted to generate a signal to indicate that the particular string **50** is varying from perfect tune. For example, if the first photodetector detects the light source, a yellow signal lamp is lit, signaling the musician to tighten the string, but if the second photodetector detects the light source, a red signal lamp is lit, signaling the musician to loosen the string. The signal is extinguished when perfect tune is again achieved. Thus, visual tuning can be achieved using media other than the musician's eyes to detect changes in string tension and tune.

In yet another embodiment, the photodetector signals may trigger automatic tuning correction without direct intervention by the musician. U.S. Pat. No. 6,437,226, the entirety of which is incorporated herein by reference, discloses a system in which a transducer detects a string vibration, which is then analyzed to determine if it is in proper tune. If the string is out of tune, motors are actuated to tighten or loosen the string to restore it to proper tune. In the present embodiment, such

motors may be actuated by the photodetector signals without the need of detecting and analyzing string vibrations. Strings may be automatically kept in tune without requiring sounding of the string.

In the embodiment illustrated in FIGS. 2-4, the string mounting system 70 is attached to the guitar body 33 by a frame 72 that attaches to the outside of the body 32. In another embodiment, the string mounting system 70 may employ a frame incorporated within and supported by the body 32 of the guitar 30. Components such as the spring tubes 82 may be at least partially hidden from view. In a still further embodiment, rather than a plurality of spring tubes, a spring box is provided, each box containing multiple springs. In yet further embodiments, rather than using boxes or tubes, the first end 84 of each spring 71 may even be attached to a frame portion that may be incorporated into the body of the guitar.

In still further embodiments, the springs can be at least partially embedded in the body of the guitar and may act in a direction transverse and/or opposite to the direction of the string. In such embodiments, the spring may be connected to the string by a pulley, lever, cam, or other mechanical interface to provide a mechanical advantage, disadvantage, and/or redirect the spring tension.

With reference next to FIG. 5, another embodiment of a guitar 130 employing a string mounting system 134 is illustrated. In the illustrated embodiment, the string mounting system 134 uses a set of six string tensioners 135 attached to the face 62 of the guitar body 32 and arranged side by side. One tensioner 135 corresponds to each musical string 50. As will be discussed in more detail below, each tensioner 135 uses a spring 138 to supply tension to the corresponding string 50. However, a spring force modulating member 140, such as a cam, is interposed between the string 50 and the spring 138 so that the actual tension applied to the string 50 by the spring 138 is not necessarily the same as the tension of the spring 138. Most preferably, the modulating member 140 is adapted so that the change in the tension supplied to the string by the spring upon a corresponding change in spring length is not linear. More specifically, the change in force actually applied by the spring 138 to the string 50 as the spring 138 changes length is modulated and preferably tempered by the mechanical member 140 interposed between the spring 138 and the string 50. In the illustrated embodiment, the modulating member 140 functions as a mechanical interface between the string 50 and the spring 138.

With reference next to FIGS. 6-9, several views are provided of a preferred embodiment of a string tensioner 135. The illustrated string tensioner 135 comprises an elongate body 142 having a top surface 144 and having a bottom surface 146 that is adapted to be attached to the front face 62 of the guitar 130. The tensioner body 142 has a first end 148 and a second end 150. Preferably, the elongate body 142 is positioned on the guitar body 62 so as to be generally aligned with a corresponding guitar string 50. The first end 148 is generally closer to the neck 34 than the second end 150, which is closer to a rear of the guitar 130.

A first portion 152 of the tensioner body 142 is defined generally adjacent the first end 148. An offset section 154 is interposed between the first portion 152 and a second portion 156 of the tensioner body 142, which is defined on a side of the offset section 154 opposite the first portion 152. As such, a longitudinal center line 160 of the first portion 152 preferably is generally parallel to but spaced from a longitudinal center line 162 of the second portion 156, as best shown in FIG. 7.

A depending portion 164 extends downwardly and, preferably, forwardly from the first portion 152. Preferably a

cavity 166 is formed in the guitar body 32 (see FIG. 12) to accommodate the depending portion 164 and other parts of the string tensioner 135 that are disposed below the bottom surface 146 of the tensioner body 142.

A plurality of mounts 170 preferably are provided for engaging the guitar body 32 and holding the string tensioner 135 in place. In the illustrated embodiment, three apertures 172A-C are formed in the second portion 156 of the tensioner body 142. Each aperture 172A-C is configured to accommodate an elongate fastener 174 adapted to extend into the guitar body 32. In one embodiment, the fasteners 174 comprise screws. In another embodiment, the fasteners 174 comprise bolts. In still another embodiment, bolt receivers (not shown) are embedded into the guitar body 32 and the fasteners comprise bolts adapted to engage the bolt receivers so as to hold the string tensioner body 142 firmly in place on the guitar body 32.

With continued reference to FIGS. 6-9, an elongate aperture 180 is formed through the second portion 156 of the tensioner body 142. A spring force modulation member 140 is adapted to fit generally within and through the elongate aperture 180. The modulation member 140 is connected to the body 142 by a pivot 182. In the illustrated embodiment, the pivot 182 comprises an axle extending transversely across the elongate aperture 180. The modulation member 140 rotates about the pivot 182. In the illustrated embodiment, the pivot 182 comprises an axle. It is to be understood that other structures may be employed. For example, in another embodiment, a wedge-shaped member having a relatively narrow upper edge, also sometimes referred to as a "knife pivot", is adapted to support the modulation member 140. The modulation member 140 may thus rock about the upper edge, enabling pivoting with very little friction.

A cam portion 184 of the modulation member 140 extends generally upwardly from the pivot 182 and comprises a string receiver 190. As illustrated, the string receiver 190 preferably comprises a saddle 192 or string track 192 adapted to accommodate and hold the guitar string 50 therein as shown in FIGS. 5 and 6. The saddle 192 preferably is defined by an elongate cavity 194 between a pair of projecting portions 196. (See FIG. 7.) A base or floor 197 of the saddle 192 preferably is arcuate, preferably generally matching the arc of a radius 198 measured from the pivot 182 to the base 197 of the saddle 192. Preferably, the distance 198 from the pivot 182 to the base 197 of the saddle 192 is generally constant along the length of the saddle 192. However, in other embodiments, the radius may vary along the length of the saddle 192.

An arm 200 of the force modulating member 140 extends generally rearwardly and through the body 142 to a point below the tensioner body bottom surface 146. A string connector 202 preferably extends upwardly from the arm 200 and is spaced from the string receiver 190. In the illustrated embodiment, the string connector 202 comprises a generally cylindrical rod 204 adapted to engage a corresponding connector 206 disposed on the end 54 of the musical string 50. Preferably, the connector 206 on the string 50 comprises an eyelet that slips over the rod 204. It is anticipated that other string connecting structures may be used in other embodiments.

A spring mount 210 is provided on the modulating member arm 200 generally below the bottom surface 146 of the body 142. Preferably, the spring mount 210 comprises a pin 212 adapted to accommodate an end of a tension spring 138. The pin 212 can be a rod, axle, bolt, screw, or other suitable structure. In the illustrated embodiment, spring tension is communicated to the arm 200 via the pin 212. Further, a distance 214 between the modulating member pivot 180 and

11

the spring mount pin 212 is fixed, and helps define the proportion of spring tension communicated through the arm 200 to the associated string 50.

A stop engagement portion 220 of the arm 200 extends rearwardly relative to the spring mount 210 and, preferably, below the bottom surface 146 of the tensioner body 142. A stop aperture is formed through the tensioner body 142. Preferably, a stop bolt 224 is threadingly advanced through the aperture. The stop bolt 224 is configured to engage the stop engagement portion 220 of the arm 200 to define a limit to rotation of the arm 200 in a counter-clockwise direction.

Continuing with reference to FIGS. 6-9, preferably, a plurality of marks 230A-B are provided on the force modulation member 140 for reference purposes. Additionally, preferably an indicator member 232 extends upwardly from the tensioner body 142 and is generally aligned with the pivot 180. The indicator member 232 preferably includes a tip 234. In use, the rotational position of the modulating member 140 relative to the tensioner body 142 can be gauged by the position of the reference marks 230A-B relative to the indicator member tip 234.

Preferably, an elongate guide member 236 depends from the first portion 152 adjacent to the first end 148 of the body 142. Preferably, the guide 236 terminates in a stop 238 attached thereto. In the illustrated embodiment, an elongate adjustment bolt 240 also depends from the depending portion 164 of the body 142 in a direction generally parallel to the elongate guide 236. In the illustrated embodiment, the guide 236 and bolt 240 extend in a direction generally downwardly and forwardly from the tensioner body 142. Preferably, the adjustment bolt 240 is threaded. An elongate shank 242 of the adjustment bolt 240 fits through an aperture 244 defined through the tensioner body 142, and a bolt head 246 is accessible through the top surface 144 of the body 142 so that the adjustment bolt 240 can be rotated through the use of a tool or the like. Since the adjustment bolt head 246 is disposed in the first portion 152, which is offset relative the second portion 156, the bolt head 246 is not aligned with the musical string 50 corresponding to the tensioner 135 (see, for example, FIG. 17). As such, a tool can access the bolt head 246 without interfering with the string 50.

A shuttle 250 is provided over the elongate guide 236 and adjustment bolt 240. The shuttle 250 preferably comprises a first aperture 252 adapted to fit slidably over the elongate guide 236 and a second, threaded aperture 254 adapted to mate with the threads of the adjustment bolt 240. As such, when the adjustment bolt head 246 is rotated, the shuttle 250 is advanced or retracted along the bolt 240 and guide 236. For instance, FIGS. 6-8 show the shuttle 250 in a first position along the adjustment bolt 240, and FIG. 9 shows the shuttle 250 in a second position along the adjustment bolt 240. Rotation of the bolt effectuates such changes in shuttle position.

With continued reference to FIGS. 6-9, the shuttle 250 preferably additionally comprises a spring mount 260 having pin 262 such as an axle, rod, bolt, screw, or other structure adapted to engage an end of the tension spring 138. The tension spring 138 preferably has first and second opposing ends 264, 266. The first end 264 of the spring 138 is attached to the spring mount 210 on the modulation member arm 200; the second end 266 of the spring 138 is attached to the spring mount 260 of the shuttle 250. As such, a longitudinal axis 270 of the tension spring 138 extends between the pins 212, 262 of the modulating member spring mount 210 and the shuttle spring mount 260. Spring force is directed along this axis 270.

With reference next to FIGS. 5-12, in a multi-string instrument, such as a guitar 130, preferably a plurality of string tensioners 135 are arranged side-by-side generally abutting

12

one another, as depicted in FIGS. 5 and 10. In the illustrated embodiment, six string tensioners 135 are provided side-by-side to appropriately secure and provide tension to the six musical strings 50 of the guitar 130. As best shown in FIGS. 5 and 12, preferably the string tensioners 135 are attached to a front face 62 of the guitar body 32. Components of the tensioners 135 that depend below the bottom surface 146 of each tensioner body 142 extend into the cavity 166 formed in the body 32 of the guitar 130. The guitar body cavity 166 can extend through the entire guitar body 32, and thus provide an access 274 through the back, as suggested by FIG. 12. In another embodiment, an access door may be provided to selectively close the cavity 166 through the back 74 of the guitar body 32. In still another embodiment, the guitar body cavity does not extend clear through the guitar body.

With specific reference next to FIG. 6, certain functions and properties of the individual string tensioners 135 are presented. As illustrated in FIG. 6, each spring 138 extends between spring mounts 210, 260 defined on the force modulating arm 200 and the shuttle 250, respectively. As is typical with coil springs, a length 278 of the spring 138 determines the degree to which the spring has elongated, which in turn determines the magnitude of force exerted by the spring. As shown, since the adjustment bolt 240 is angled relative to the spring's line of action, or longitudinal axis 270, movement of the shuttle 250 has the effect of increasing or decreasing the length 278 of the spring 138 for a given position of the modulating member arm 200. However, when the shuttle 250 is held fixed in a position, and thus the shuttle spring mount 260 is fixed, rotation of the force modulating member 140 about the pivot 182 correspondingly results in linear movement of the modulating arm spring mount 200, which linear movement increases or decreases the length 278 of the spring 138. Specifically, when the modulating member 140 is rotated counter-clockwise, the length 278 of the spring 138 increases, thus resulting in an increase of the force exerted by the spring. With additional reference to FIG. 13, a plot is presented of a sample embodiment having structure similar to the illustrated tensioners 135. In the illustrated embodiment, as the modulating member 140 is rotated counter-clockwise, the force exerted by the spring in response to spring elongation increases generally linearly over the illustrated limited range of rotation (here 100°).

With continued reference to FIG. 6, the spring 138 has a line of action generally along its longitudinal axis 270. The longitudinal axis 270 is spaced a lever arm distance 280 from the pivot point 182. The lever arm distance 280 determines the mechanical advantage (or, in some embodiments, mechanical disadvantage) the spring 138 has relative to its load, the string 50, which has a radius 198 spacing from the pivot point 182. When the shuttle 250 is held in a fixed position, rotation of the force modulating arm 200 results in a change in the lever arm distance 280.

With additional reference to FIG. 6A, a schematic diagram represents certain relationships of the embodiment illustrated in FIG. 6. For example, the pivot point 182, string saddle base 197, pin 212, and pin 262 are represented, as well as lines 198, 214, 278 and (b) representing the distances between these points.

With additional reference to FIG. 14, a plot is presented showing the change in lever arm distance 280 for the spring 138 as the modulating member 140 is rotated counter-clockwise through a limited range of modulating member rotation (here 10°). As shown, the lever arm 280 distance decreases generally linearly as the modulating member 140 is rotated counter-clockwise.



## 13

As just discussed, as the force modulating member **140** is rotated counter-clockwise, such as when the string **50** is being tightened on the guitar, the spring **138** elongates, and spring tension thus linearly increases. However, at the same time, the lever arm distance **280** upon which the spring **138** is acting linearly decreases. These effects act in opposition to one another, thus creating a special advantageous effect on string tension during such angle changes. For example, with additional reference to FIG. **15**, a plot of string tension actually delivered to the string **50** from the spring **138** via the force modulating member **140** is illustrated. This plot shows the combined effect of the changing spring force and lever arm distance as the modulating member rotates.

It should be appreciated that the scale of FIG. **15** is highly amplified, exaggerating the curvature. In fact, this is a relatively flat curve over the small anticipated angle of operation of the modulating member **140**. For instance, for a preferred embodiment, the modulating member **140** operates in a range between about two degrees to seven degrees of angle. In the illustrated embodiment, over this five-degree range of rotation, the string tension changes within a range of only about 0.02 pounds. It should be appreciated that 0.02 pounds of tension corresponds roughly to one cent of pitch, which corresponds to such a small change in the pitch of the tone emitted by the corresponding string that the change of pitch is not detectable by the human ear. As such, even if during play or other use the string elongates up to about five degrees of rotation of the modulating member **140**, the change in tune will not be aurally detectable.

For a stringed instrument such as a guitar, the most typical reason the instrument goes out of tune is that over time the strings stretch or otherwise relax, and thus the tone emitted by that string goes flat as the tension is lost. Stretching of the string and/or other factors such as friction at the guitar nut or bridge, and string interference when wound about the tuning pegs, or environmental factors such as humidity and heat, among other possible factors, can cause a string to elongate, and thus slacken.

In an instrument employing a mounting system **134** as discussed herein, as the string **50** elongates, the spring **138** maintains tension on the string **50**, and thus counteracts slackening. More specifically, the force modulating member **140** rotates clockwise. Although such clockwise rotation may result in a decrease of the force exerted by the spring **138**, the corresponding increase in lever arm **280** for spring operation assures that tension will remain at or near perfect-tune levels, as portrayed in the example plots of FIGS. **13-15**. Since musical strings typically elongate only very short distances, a string tensioner **135** having a relatively small operating range, such as 10 degrees, 7 degrees, 5 degrees, or less, provides plenty of range for taking up the slack in the musical string as it elongates.

Notably, certain factors can cause the string to attempt to contract, and thus tighten. Such tightening may cause the string to go out of tune. The illustrated mounting system **134** also maintains an appropriate tension on the string **50** as the string contracts, thus counteracting tightening.

In a typical guitar, as a string elongates or attempts to contract, the string ends remain fixed, thus, a string that elongates becomes slack, and a string that attempts to contract tightens. In the illustrated embodiment, the second end **54** of the string is attached to the modulating member **140**, which enables the second end **54** of the string to move. By allowing the second end **54** to move as the string elongates or contracts, but still applying an appropriate tension, the illustrated embodiment counteracts slackening and tightening.

## 14

Applicants have tested embodiments of structures for modulating spring forces. Such an analysis, though performed with an embodiment having features resembling that of FIG. **6**, employs principles that can be used in embodiments having other structures. With reference again to FIG. **6A**, distances and mathematical relationships of portions of the string tensioner **135** are represented schematically. This schematic representation will be used to discuss a specific example embodiment. For purposes of the discussion, the length **214** of the mount arm will be referred to as "a", the distance between the pivot point **198** and pin **262** will be referred to as "b", the length **278** of the spring will be referred to as "c", and the lever arm **280** of the spring will be referred to as "L". The angle between a and b will be referred to as  $\theta$ ; and the angle  $\delta$  is a complementary angle to  $\theta$ .

In one example:

a=0.95 in.;

b=1.45 in.;

c<sub>0</sub>=spring free length=1.545 in.;

c=stretched length of spring (this parameter changes as the arm **200** rotates);

k=9.492 lb./in.; and

spring pre-load=1.344 lb.

The tension T in the spring is calculated by:  $T=k(c-c_0)+1.344$  lb. Also, per the law of cosines,  $c^2=a^2+b^2-2ab\cos(\theta)$ . Since  $\theta=180-\delta$ ,  $\cos(180-\delta)=-\cos(\delta)$ . Thus:  $c^2=a^2+b^2+2ab\cos(\delta)$ , and  $c=(a^2+b^2+2ab\cos(\delta))^{1/2}$ .

Per properties of trigonometry,  $L=b\sin(\alpha)$ . Per the law of sines,  $\sin(\alpha)/a=\sin(\theta)/c$ . Thus,  $\sin(\alpha)=(a/c)\sin(\theta)$ . By trigonometric identities,  $\sin(\theta)=\sin(180-\delta)=\sin(\delta)$ . Thus,  $\sin(\alpha)=(a/c)\sin(\delta)$ . Solving for L:  $L=(ab/c)\sin(\delta)$ .

Using the mathematical relationships discussed above, Table A was prepared to show force characteristics of the sample embodiment relative to angle  $\delta$ :

TABLE A

$\delta$ (deg)	Spring Length c	c - c <sub>0</sub>	Tension in Spring T	Lever length L	Torque (TL) at pivot 182
0	2.40000	0.855	9.45966	0.00000	0
2	2.39965	0.85465	9.456341	0.02003	0.18945
4	2.39860	0.85360	9.446385	0.04006	0.37843
6	2.39685	0.85185	9.429796	0.06007	0.56648
8	2.39441	0.84941	9.406579	0.08007	0.75315
10	2.39126	0.84626	9.376742	0.10003	0.93796
15	2.38036	0.83536	9.273261	0.14978	1.38892
20	2.36513	0.82013	9.128701	0.19920	1.81843
25	2.34561	0.80061	8.943374	0.24819	2.21965
30	2.32183	0.77683	8.717683	0.29664	2.58602
35	2.29385	0.74885	8.452119	0.34444	2.91127
40	2.26174	0.71674	8.147266	0.39149	3.18954
45	2.22555	0.68055	7.803797	0.43766	3.41542
50	2.18538	0.64038	7.422478	0.48286	3.58400
55	2.14131	0.59631	7.004167	0.52696	3.69091
60	2.09344	0.54844	6.549818	0.56985	3.73242
65	2.04189	0.49689	6.060482	0.61141	3.70546
70	1.98677	0.44177	5.537312	0.65152	3.60768
75	1.92822	0.38322	4.981566	0.69005	3.43751
80	1.86639	0.32139	4.394614	0.72684	3.19420
85	1.80142	0.25642	3.777948	0.76176	2.87791
90	1.73349	0.18849	3.133191	0.79464	2.48975

As shown in the data for the specific example presented above, the range of  $\delta$  at which the torque applied by the spring to the pivot point **182** changes the slowest is between about 55-65°. Thus, preferably the above embodiment operates so that the string **50** is at a perfect-tune tension when the angle  $\delta$  is between about 55-65°. Even more preferably, the embodiment is adapted to operate within a smaller range of angular change, such as less than about 5°. Further, this example

15

shows that operating parameters, specifically the lengths  $a$ ,  $b$ , and  $c_0$ , and any preloading of the spring, determine the range of degrees through which there is relatively small change in torque applied by the spring to the pivot point.

It is to be understood that a "sweet spot", or point at which the rate of change of the torque applied to the pivot point reaches zero, can be determined. Such a point can be calculated by finding the point at which  $T \cdot L$  transitions from an increasing to a decreasing calculated value. Most preferably, the string mounting system is configured so that anticipated string elongation is confined to a range of arm rotation (less than  $10^\circ$  or, more preferably, less than  $5^\circ$ ) about this sweet spot in order to minimize the magnitude of the change in tension applied by the spring to the string upon elongation of the string. Such an operational range can be defined simply as an expected range of angular operation or can be mechanically determined by the device itself. For example, in the string tensioner **135** of FIG. 6, the stop engagement portion **220** engages the stop bolt **224** to prevent counterclockwise rotation beyond a particular angular position. In another embodiment, a forward stop engagement portion (not shown) extends from the modulating member and is adapted to engage the tensioner body **142** at a location forwardly of the elongate aperture **180** so as to prevent clockwise rotation beyond a desired angular position.

Additionally, it is to be understood that a diagram such as is depicted in FIG. 6A can be generated for many types and designs of lever-arm-type structures that may look different than the illustrated embodiment. For example, in the illustrated embodiment, pin **262** is the point of action of the spring that pulls on the end **212** of the mount arm **200**, and the spring is mounted between pins **212** and **262**. In other embodiments, the spring is not necessarily directly attached to pins **262** and/or **212**, but acts on the arm mount **212** through the point labeled **262** via cables, pulleys, other members, special geometry, and the like.

The above example illustrates a design having a preferred operating range based on optimizing factors related to the distances  $a$ ,  $b$  from mounts to the pivot point. It is to be understood that, in another embodiment, the radius **198** can also be varied over the preferred operating range so as to vary the effective moment of the cam portion **184** of the modulation member **140**, thus counteracting the small changes in torque at the pivot **182**. For example, in one embodiment that may be used in conjunction with properties such as disclosed above in connection with Table A, the radius **198** is lesser when  $\delta$  is  $60^\circ$  than when  $\delta$  is  $55^\circ$  or  $65^\circ$ . As such, the changing radius **198** compensates for the slightly increased torque ( $T \cdot L$ ) at  $60^\circ$  so that the tension applied to the musical string **50** is even closer to a constant magnitude.

In still another embodiment, instead of or in addition to a lever-arm-type spring structure as described above, the cam **184** may be replaced by a spiral-tracked conical cam structure, similar to a fusee, that can compensate for a changing applied force by providing a corresponding change in effective moment arm for applying the force to the musical string.

Applicants have had marked success in employing the structure just described above in connection with FIGS. 5-15. Specifically, the mechanical structure **140** interposed between the spring and the string modulates the relationship between the force exerted by the spring and the tension actually applied to the string so that they are not linearly related. Further, the mechanical structure provides a relatively simple and easily constructed structure that will fit within the compact confines of a typical musical instrument such as an electric or acoustic guitar. However, it is to be understood that Applicants contemplate that other types or forms of mechani-

16

cal structures interposed between a spring and a corresponding musical string can also modulate the effect of forces exerted by the spring on the corresponding string. More specifically, Applicants contemplate that other mechanical interface structures can effectively flatten a string tension curve relative to its corresponding spring's tension curve by using various mechanical structures, such as cams, lever arms, pulleys, gears, or the like in various configurations.

In order to tune an embodiment as depicted in FIG. 6, preferably the shuttle **250** of the string tensioner **135** is first positioned at an ideal position for the tension of the corresponding musical string **50**. As such, when the string **50** is connected to the force modulating member arm **200**, strung over the string receiver **190** and into the tuning knobs **48** of a guitar, and then tightened, it will achieve ideal tune when at a position very similar to that depicted in FIG. 6, which shows the tensioner reference tip **234** aligned with a preferred tune reference mark **230A** on the string cam **184** of the modulating member **140**. However, in order to fine tune the positioning of the shuttle **250** for a particular string tension, the user may use an iterative process in which the shuttle **250** is moved and tuning knobs **48** are correspondingly moved so that perfect tune is achieved at a point when the tensioner body indicator tip **234** is aligned with the preferred reference line **230A** of the cam portion **184**. Although the shuttle **250** position is adjustable, it preferably remains in a fixed position during play and after initial tuning.

Another preferred method of tuning can be performed without first adjusting the shuttle **250**. In this embodiment, the string is first tuned in a manner as with a conventional guitar. During this process, the forward or rear stop engagement portion **220** usually engages, preventing rotation of the modulating member **140** and removing the spring from consideration in string tuning. Once the string is appropriately tuned, the shuttle is adjusted until the stop engagement portions are no longer engaged.

As such, a visual indicator of perfect tune is provided. As discussed above, during play, as the string **50** elongates and the string tensioner **135** compensates for such elongation without substantially changing the actual string tension, the fact that string elongation has occurred will be visually and mechanically reflected since the tip **234** will no longer be aligned with the preferred line **230A**, thus indicating a change in angular position of the modulating member **140**. Thus, a musician will be able to tell when the string **50** has stretched by observing the visual indicator, even though the string pitch or tune likely will not have changed to a magnitude that is audibly detectable by the human ear. By periodically checking his instrument, the musician can detect when a string **50** has moved from the perfect tune position, and will be able to use the tuning knobs **48** to incrementally tighten the string **50** to return the string **50** to the perfect tune position indicated by the aligned tip **234** and reference line **230A**.

One popular guitar playing method is for the guitarist to "bend" notes during play. This is accomplished when the musician pushes a string **50** against the fretboard **42**, and then further deflects the string relatively radically, thus changing the tension of the string **50** and correspondingly changing the note emitted by the string. In a preferred embodiment, after the instrument has been tuned, the user tightens the stop bolt **224** to a point where an end of the stop bolt **224** is near but either slightly spaced from or barely engaging the corresponding stop engagement arm **220**. As such, when a guitarist bends notes by radically deflecting the strings **50**, rather than rotating the modulating member **140** counter-clockwise, and thus cancelling or muting the bend effect, the engagement arm **220** will engage the stop bolt **224**, preventing such

counter-clockwise rotation. Thus, the spring **138** is removed from consideration and prevented from softening the bend effect, and a guitarist can obtain a substantial note bending effect through normal play.

In yet another embodiment, an arrangement may be provided to aid in setting the position of the stop bolt **224**. In this embodiment, the stop bolt is electrically energized. An electrical contact is disposed on the stop engagement arm **220** and aligned with the bolt so that when the bolt touches the contact an electrical circuit is completed. Completion of the electrical circuit generates a signal. Such a system may be especially helpful when setting the position of the stop bolt. For example, an electric guitar may have a bend stop setting in which detection of the signal indicating completion of the electric circuit results in some effect, such as cutting off the signal to the amplifier, actuation of a lighting or aural effect, or the like so that the user will know that the arm **220** and bolt **224** are engaged. The user then backs the bolt **224** just until the signal stops, indicating that the arm **220** and bolt **224** are not engaged, but are positioned very close to one another. In this position, engagement of the arm **220** and bolt **224** is nearly instantaneous when the guitarist deflects strings to get the bending effect. After setting the arm **220** and bolt **224** position, the guitar setting preferably is changed so that, during play, the signal does not interfere with play.

In another embodiment, the arm **220** and bolt **224** may be intentionally set relatively far from each other so that the bend effect is, generally, avoided. Such a setting may be particularly preferred by beginner guitarists who, due to inaccurate finger positioning, may unintentionally bend notes, resulting in a too-sharp emitted note.

In still another embodiment, an electrical circuit that is selectively completed when the bolt **224** and arm **220** are engaged may be employed to intentionally trigger certain effects during a performance. For example, in one embodiment, completion of the circuit may trigger an aural effect, such as automatically triggering the distortion effect of the electric guitar and/or amplifier. In another embodiment, lights such as LEDs may be attached to the guitar, and completion of the circuit may trigger a visual effect such as temporarily turning on some or all of the LEDs.

In still another embodiment, the guitar may be electronically connected, via wire or wireless connection, to a computer system, and completion of the circuit may be detected by the computer system, which may control other effects. For example, in a stage show, certain lighting, pyrotechnic, or other effects may be computer-controlled. Upon detection of a signal from the guitar indicating string bending, the computer system thus can generate a lighting or other effect to enhance the aural effect already being generated by the guitar.

In yet another embodiment, a contact on the arm **220** includes a pressure sensitive transducer so that the signal generated upon completion of the circuit can also include an indication of the intensity of the bending effect. Each of the above-discussed embodiments may accordingly be enhanced and modified depending on the sensed intensity of the bending effect.

It is to be understood that various electrical circuit configurations may be employed to both electrically indicate engagement of the bending effect and the intensity of the effect. It is also to be understood that the guitar, amplifier, or other equipment preferably is set up to allow a user to change the setting between a setup configuration, no-effect configuration, and/or special-effect configuration, or other desired configurations.

In the embodiment depicted in FIGS. 5-12, the guitar **130** is provided without a separately formed bridge. In this

embodiment, the string receiver **190**, specifically the saddle **192**, functions as a bridge. With reference next to FIGS. **16** and **17**, a separate bridge **290** may be interposed between the string tensioners **135** and a playing portion **63** of the tightened strings **50**. In the illustrated embodiment, the bridge **290** comprises a plurality of bridge members **292**, each having a roller **300** adapted to function as a bridge for a corresponding string. In one embodiment, each bridge member **292** and corresponding roller **300** is adjustable over a short range so that the position of the roller **300** relative to the string **50** and other rollers can be adjusted if desired. Additionally, the illustrated bridge **290** is attached to the guitar body **32** by fasteners **302** that extend through first and second apertures **304**, **306**. The first and second apertures **304**, **306** are elongate so that, upon loosening of the fasteners **302**, the entire bridge **290** may be moved longitudinally and then retightened in a desired position. It is to be understood that guitar bridges having various structures, including non-adjustable structures that use structures other than rolling bridge members, may also be used in accordance with preferred embodiments.

With reference next to FIGS. **18** and **19**, another embodiment of a string tensioner **310** is provided. This embodiment is also adapted for use with a guitar. In this embodiment, the string tensioner **310** comprises a single frame **312** adapted to be used to tighten six adjacent musical strings. The single frame **312** employs six elongate apertures **314**. A force modulating member **320** is pivotally mounted in each elongate aperture **314**. Mounting fasteners **322** are provided to attach the frame **312** to a guitar body.

The illustrated string tensioner **310** operates on principles similar to those employed in the embodiment discussed above, but may have different structure. For instance, the illustrated embodiment includes a shuttle **324** riding over an adjustment bolt **330** and not having a separate guide member. Preferably, the adjustment bolt **330** is rotatably secured adjacent the bolt head **322** and adjacent a distal end **334** of the bolt **330**. The shuttle **324** moves linearly as the bolt **330** is rotated. Additionally, rather than employing a pin for mounting of the spring ends, the shuttle **324** and the force modulating member arm **320**, both comprise an aperture **336** through which ends of a coiled tension spring **138** can be inserted.

Further, embodiments described above showed the stop bolt **224** as having a hex bolt construction requiring a tool for adjustment. In the illustrated embodiment, the stop bolt comprises a winged head **340** that can be easily hand-adjusted without using of tools. This or other constructions can be used for other structures. For example, in another embodiment the adjustment bolt **330** may be adapted to be adjustable without the use of separate tools and/or may be accessible for adjustment through the back of the guitar. In still another embodiment, the guitar may be modified to have a tool receiver portion or cavity sized and adapted to store an adjustment tool for adjusting the adjustment bolt and/or other components so that the tool is always with the instrument.

In accordance with yet another embodiment, a roller bridge **340** may be provided having a roller structure **342** dedicated to each string **50**. Preferably, the roller structures **342** are adapted to generate very little friction during use. As such, an embodiment is contemplated in which each roller structure **342** comprises a roller **344** adapted to rotate about an axle **346** that is rotatably mounted in an axle support member **348**. In one embodiment illustrated in FIG. **18**, the axle **346** has a small diameter, such as about 0.030 in., and the roller **344** has a relatively large diameter, such as about ¾ in. As such, a ratio of the roller diameter to the axle diameter is about 25. An embodiment having such a ratio can be expected to have relatively small friction losses during relatively small rota-

tions such as when checking and modifying tune of a musical instrument employing string tensioners **135**, **310** as discussed herein. Preferably, a low-friction roller bridge is provided having a roller diameter to axle diameter ratio greater than about 10; more preferably greater than about 15; and still more preferably greater than about 20.

In the embodiment illustrated above in connection with FIGS. 5-12, the line of action **270** of the spring **138** operates about a lever arm distance **280** that is greater than a lever arm distance **198** of the string cam member **184**. As such, the spring **138** has a mechanical advantage, and thus is capable of exerting a tension on the string **50** that is greater than the force generated by the spring **138**. This structure enables a smaller, lighter and less expensive spring to be employed than if there were an end-to-end connection between the string and the spring. This also facilitates a structure in which the line of action **270** of the spring **138** is in a direction generally transverse to the corresponding string **50**. It is to be understood that several different structural designs may employ the inventive principles taught by this embodiment, but may look quite different than the illustrated embodiment.

In still another embodiment, a single spring can apply tension to two or more strings simultaneously. In embodiments in which the corresponding musical strings are designed to operate at different string tensions, a different lever arm distance preferably is provided in the corresponding force modulating member **140** so that the same spring can apply differing actual tensions to the corresponding strings. Preferably, the rate of change in operating lever arm of the spring as the modulating member rotates is identical for both strings so that the magnitude of force actually applied to the strings changes uniformly for each of the attached strings.

The illustrated embodiments have employed coil-type springs to apply tension to the strings. It is to be understood, however, that various other types and configurations of springs may be employed. Further, the term "spring" should be understood to be a broad term including embodiments as discussed above, and, generally, structures that can store and mechanically impart energy, or force, upon a string directly or through a mechanical interface, and may include a single spring member or a plurality of members that work together in some way.

For example, gas springs can be employed to provide appropriate tension while maintaining compact size. Several gas spring options are available, and such gas springs can be obtained from McMaster-Carr and other manufacturers. Another capable example is a flexible bar or the like that may function as a spring. Such a bar could even have a unique geometry resulting in specially-tailored spring action directions that inherently create a moment arm relative to a connection point, thus including spring and force modulation in a single member.

With reference next to FIG. 20, another embodiment is provided in which a constant torque spring, such as the NEGATOR Constant Torque Spring Motor, which is available from Stock Drive Products/Sterling Instrument, can be mechanically connected to a musical string and configured to apply a substantially constant tension to the string. In the illustrated embodiment, the constant torque spring motor **350** comprises a first coil **352** mounted to the musical instrument at a first mount **354**, and a second coil **356** that is mounted to a rotatable bar **358**. A threaded lever arm **360** extends from the bar **358** and has a knob **362** adapted so that the arm **360** can be rotated. A shuttle **364** is disposed over the threaded arm **360**, and a musical string **50** is attached to the shuttle **364**. As such, the constant force spring **350** applies a substantially constant torque to the bar **358**, which in turn exerts a constant tension

on the string **50** by way of the lever arm **360**. Since the lever **360** is adjustable, a user may vary the effective moment arm of this arrangement, and thus custom-tune the tension actually applied to the string by the constant force spring motor **350**.

With next reference to FIG. 21, a constant force spring **370**, such as is available from Vulcan Spring & Mfg. Co. of Telford, Pa., comprises a single roll of pre-stressed spring steel having a mount **372** attached to the body of the musical instrument. An attachment end **374** of the spring is attached to a lever arm **380**, which is slidably mounted onto a rotatable bar **382**. In the illustrated embodiment, a portion of the lever arm **380** has a plurality of gear teeth **384**. A rotatable gear **386** is mounted onto the bar **382**, and is actuable by a user via a knob **388**. When the knob **388** is twisted, the gear teeth engage, sliding the arm **380** and changing the effective moment arm length of the lever **380**. In the illustrated embodiment, a track portion **390** of the bar **382** contains the lever arm **380** in place.

With continued reference to FIG. 21, a second lever **392** is also provided on the bar **382**, and the musical string **50** is attached to the second lever **392**. As such, the constant force spring **370** applies a substantially constant force which has a mechanical advantage or, in other embodiments, disadvantage relative to the string **50**. Also, by adjusting the effective moment arm length of the lever **380**, the user can fine tune the tension that is applied to the string **50** in order to attain and maintain a desired tune.

Due to the rolled structure of the constant force spring **370**, the applied force of the spring varies very little from its rated level, such as less than about 1% over 20%, 40%, 60%, 80% or more of its length of operation. As such, a constant force spring can provide a consistent application of force so as to provide a consistent, near constant tension to the musical string **50**, thus enabling the string to keep substantially the same tension, and thus tune, even when the string elongates or contracts.

Although the above embodiments employ moment arms, it is to be understood that a constant force spring having a specific desired output force may be attached end-to-end with a corresponding musical string in order to apply a desired tension force to the string. The constant force spring preferably is chosen to apply the desired tension without force modulation between the spring and the string.

Although the illustrated embodiments have employed adjustable levers, it is to be understood that other structures, such as a variable radius pulley, can also be used to provide an adjustable moment arm so as to fine tune the precise tension exerted by the spring on the associated musical string.

With reference next to FIG. 22, yet another embodiment is provided in which two springs **400**, **414** operate on a single musical string **50**. In the illustrated embodiment, a first constant force spring **400** is attached at a first mount **402** to the instrument body and has an attachment end **404** attached to a first lever **410**. The string **50** is also attached to the first lever **410**, which is adapted to rotate with a rotatable rod **412**. A second spring **414** is attached to the musical instrument body at a second mount **416** and is also attached to a second lever **420** having an adjustable moment arm length by, for example, providing teeth **422** on a portion of the lever arm **420** and having a gear **424** with a user-operable knob **426** for adjusting the effective moment-arm length of the lever arm **420**.

In the embodiment illustrated in FIG. 22, the first spring **400** is adapted to provide the majority of the tension to the associated string **50**. For example, if the nominal desired tension of the string is about 21 pounds, the first constant torque spring **400** may be adapted to provide, through the

## 21

lever arm **410**, 20 pounds of tension, while the second spring **414** is adapted to provide, via the lever arm **420**, about 2 pounds of tension. As such, the two springs working in concert provide the desired tension of the associated string **50**. However, since the second spring **414** is smaller, it can be provided with more precise loading and adjustment characteristics so as to aid in easily adjusting and tuning the tension actually exerted on the string.

In another embodiment, the second spring may be a different type of spring, such as a coil-type spring. Also, the second spring may be attached to the string **50** in a manner similar to the illustrated embodiment, or through some other type of force modulating member. Since the second spring is relied upon for only a relatively small magnitude of tension, a coil spring having a relatively small spring constant may be chosen. Such a spring would have a lesser change in magnitude over a particular range of string elongation or contraction. As such, the concept of using multiple springs working together increases the options available to string mounting system designers.

With reference next to FIGS. **23A** and **23B**, yet another embodiment of a string tensioner **135a** is provided. In this embodiment, the string tensioner comprises a body **142a** that supports a spring force modulating member **140a** that is adapted to rotate in a limited range about a pivot **182a**. The modulating member **140a** comprises an arm **200a** having a string receiver **190a** is adapted to receive and support a musical string **50**. The arm **200a** also includes a spring mount **210a** adapted to engage a first end of a spring **138a**.

The body portion **142a** supports a threaded adjustment bolt **240a** upon which a shuttle **250a** is arranged. The longitudinal position of the shuttle **250a** along the bolt **240a** can be adjusted by rotating the bolt using the knob **246a**. The shuttle **250a** includes a spring mount **260a** adapted to receive a second end of the spring **138a**.

In this embodiment, the force modulating member **140a** rotates about the pivot **182a**, and force from the spring **138a** is modulated and provides tension to the string **50** in a manner functionally similar to the embodiment discussed in connection with FIGS. **5-12**. A stop engagement portion **220a** of the modulating member **140a** is adapted to engage a stop surface **224a** formed on the body **142a** so as to limit the range of rotation of the modulating member **140a**. FIG. **23A** shows the tensioner with the stop **220a** engaged, and FIG. **23B** shows the tensioner **135a** rotated away from the stop **220a**.

In embodiments discussed above in connection with FIGS. **2-4**, the springs **71** generally directly exert their spring force to the corresponding strings **50** without a force modulating member disposed between the spring and string. In the embodiments discussed above in connection with FIGS. **5-12**, the springs **138** exert their spring force to the corresponding strings **50** through a force modulating member. As discussed above, force modulating members of various shapes, sizes and configurations are contemplated. Applicants contemplate that aspects of the present inventions can be advantageously employed both through embodiments having direct spring-to-string force application and through embodiments in which spring force is modulated while being communicated to the string. In a particularly preferred embodiment, the spring force application is such that as the string elongates, the springs maintain tension so that the string remains within an acceptable range of tone relative to perfect-tune. In another preferred embodiment, as the string elongates, the spring continues to apply tension so that string tune changes relatively slowly as compared to a traditional

## 22

instrument. Such slowing of the process of going out of tune is valuable, even though preserving near-perfect tune is preferred.

The discussion below establishes certain mathematical relationships that may be considered when developing embodiments employing springs to supply a tension to a corresponding musical string, which tension preferably is relatively slow-changing upon stretching of the string over time and more preferably is generally constant notwithstanding stretching of the string over a range.

Certain mathematical equations include:

$$\text{frequency of vibrating string: } f = (\frac{1}{2}L) (T/d)^{1/2} \quad 1)$$

where

$L$  is the length of the string;  
 $T$  is the string tension; and  
 $d$  is the string diameter

$$\text{Young's modulus of elasticity: } \rho = F/I/(Ax) \quad 2)$$

where

$\rho$  is the modulus of elasticity;  
 $F$  is the force along some axis  $Z$  of the material;  
 $I$  is the natural length along the same axis  $Z$  of the material;  
 $A$  is the cross sectional area of the material along axis  $Z$ ; and  
 $x$  is the linear displacement (the stretch).

$$F = -Kx. \quad 3)$$

where

$K$  is the spring constant, or spring rate, of the spring.

Rearranging equation 2 we get  $F = (\rho A/I)x$ , which is equation 3 where  $\rho A/I = K$ . For steel,  $\rho$  is about 30,000,000 lbs./in.<sup>2</sup>; for nylon,  $\rho$  is about 1,500,000 lbs./in.<sup>2</sup>. As such, steel is about 20 times stiffer than nylon. However, nylon strings will have a wider cross sectional area compared with steel strings because, as equation 1 shows, density is a variable in the emitted frequency. The density of steel is about 0.28 lbs./in.<sup>3</sup> the density of nylon is about 0.04 lbs./in.<sup>3</sup>. Thus, the cross sectional area of a nylon string is about 7 times that of a steel string (0.28/0.04) if we are to keep the mass per unit length density (as used in equation 1) of the steel and nylon strings substantially the same. If the density of the strings is held constant, the same length string under the same tension will emit the same frequency.

Since  $K$  is proportional to the cross sectional area, the "stretchiness" of a nylon string with the same mass per unit length of a steel string will be 20/7 (~3 times) that of a steel string. Put another way,  $K_{\text{nylon}} = (7/20)K_{\text{steel}}$ .

In a typical guitar, the nominal string diameter of the steel high E string (the stretchiest string) is about 0.009" in diameter, and the maximum natural length of this string is about 40". From these parameters, we can calculate that the spring constant for this string is about  $30,000,000 * (0.009/2)^2 * \pi / 40 = 47.71$  lb./in. for steel, and about  $47.71 / (20/7) = 16.7$  lb./in. for nylon. The ultimate strength of steel is about 213,000 lbs./in.<sup>2</sup>; thus a steel high E string will likely fail if stretched more than about  $213,000 * \pi * (0.009/2)^2 = 13.5$  lbs. Maximum deflection of the E string at this maximum tension is  $13.5 \text{ lbs.} / (47.71 \text{ lbs./in.}) = 0.28$  inches which is, for a typical 40" guitar string, about 0.7% elongation.

Similarly, based on these assumptions and calculations, the stretchiest string (E) of the stretchiest material (nylon) of a conventional guitar will stretch about  $0.28 * (20/7) = 0.81$  inches or about 3/4" which is, for a typical 40" guitar string, about 1.9% elongation.

An additional embodiment has a structure generally similar to those disclosed above in connection with FIGS. 2-4, but may have varying relative dimensions. One such embodiment has a spring constant of about 1 lb./in. For a steel E string that deflects 0.28 inches at 13.5 lbs. of tension, the change in tension pursuant to equation 3 is 0.28 lb. Thus, the changed tension applied by the spring will be 13.22 lbs. Since, when other factors are held constant, the frequency of a string changes with the square root of the tension, the frequency can be expected to change about 1%, remaining about 99% of the original frequency. By the same reasoning, using a spring having a rate of about 2 lb./in. yields a frequency about 98% of the original-frequency. Similar calculations determine the following additional relationships: a spring rate of 0.5 lb./in. yields a frequency about 99.5% of the original frequency; a spring rate of 0.25 lb./in. yields a frequency about 99.7% of the original frequency; and a spring rate of 0.1 lb./in. yields a frequency about 99.9% of the original frequency. Further, although this discussion contemplates a directly connected embodiment such as in FIGS. 2-4, using a force modulating member can further soften spring rates to even further lessen the frequency differences with a change in string elongation.

In the 12-tone musical scale, moving down a full step (note) is achieved at a frequency that is  $2^{(-2/12)}=0.89$  times the original note. Thus, a pitch emitted within about 90% of the original frequency of a tuned string is within about 1 full step of the original pitch.

Further to the above discussion, spring arrangements can be chosen so that even larger string elongations, such as elongation by one or two inches (of a 40 in. guitar string), results in a frequency that is still 90% or more of the original, perfect-tune frequency.

In yet another embodiment, a constant torque spring motor, such as the NEG'ATOR product discussed above, or a constant force-type spring, is coupled with a string so as to apply a near-constant force even during elongation of the spring by several inches. As such, even if the spring operates on a lever arm, the change in spring tension is very small even if the string were to elongate 1, 2 or more inches, and substantially negligible for the relatively small stretch anticipated during use.

In a still further embodiment, musical string is constructed of wire manufactured according to very tight tolerances. For example, preferably a string that is adapted to be the high E string of a guitar has a nominal diameter of about 0.009 inches, and a diameter tolerance of less than 0.5%, more preferably less than 0.25%, and most preferably below 0.1%. As such, consistency of actual natural frequency of the string at a specified tension and effective length is achieved. For example, the guitar high E string nominally vibrates at 330 Hz. Applicant has determined that a string diameter that varies from the nominal diameter by  $\pm 0.25\%$  will vibrate at between 329.175 and 330.825 Hz, which corresponds to about 1.65 beats per second. Adherence to 0.1% diameter tolerances will result in under 0.66 beats per second, which is an inaudible difference in tune. Preferably, manufacturing tolerances are such that the variation from nominal frequency generates a beat frequency of less than about 2 beats per second, more preferably less than about 1.65 beats per second, still more preferably less than about 1 beat per second, and most preferably about 0.66 beats per second or less.

In connection with a tight-tolerance string, an embodiment may employ a spring having similarly tight-tolerances joined end-to-end with the string. As such, substantially no adjustments will be necessary. In such an embodiment, indicia may be provided adjacent the spring/string connection to indicate the actual tension of the string. Thus, when mounting the

string on the instrument, the user tightens the tuning knob until the spring/string connection aligns with the appropriate indicia mark. Also, if the string is to change in length due to relaxation or the like, the user may adjust the tuning knob to realign the connection with the appropriate indicia mark.

It is also to be understood that embodiments described herein can be adapted to be used with strings of various sizes, tones, lengths and the like. For instance, different guitar strings typically have an ideal (perfect tune) tension between about 10-20 lb., and sometimes between about 10-30 lb. Certain relatively large piano strings are configured so that their perfect tune tension approaches 200 lb. and, if multiple strings are combined and powered by a single spring, such tension requirement may approach 1,000 lb. It is contemplated that certain musical strings may find a perfect tune tension at or even below 5 lb. Applicants contemplate arranging embodiments to accommodate such ranges of string tensions.

Although the inventions disclosed herein have been disclosed in the context of certain preferred embodiments and examples, it will be understood by those skilled in the art that the present inventions extend beyond the specifically disclosed embodiments to other alternative embodiments and/or uses of the inventions and obvious modifications and equivalents thereof. In addition, while a number of variations have been shown and described in detail, other modifications, which are within the scope of these inventions, will be readily apparent to those of skill in the art based upon this disclosure. It is also contemplated that various combinations or subcombinations of the specific features and aspects of the embodiments may be made and still fall within the scope of the inventions. Accordingly, it should be understood that various features and aspects of the disclosed embodiments can be combined with or substituted for one another in order to form varying modes of the disclosed inventions. For instance, lighting sources discussed in connection with FIGS. 2-4 may also be employed in connection with embodiments shown in FIGS. 5-12 or any embodiments taught or suggested herein, and coil springs as shown in FIGS. 5-12 can be used in embodiments such as that shown in FIG. 22. Thus, it is intended that the scope of the present invention herein disclosed should not be limited by the particular disclosed embodiments described above, but should be determined only by a fair reading of the claims that follow.

What is claimed is:

1. A stringed musical instrument, comprising:
  - a musical string having first and second ends;
  - a first receiver adapted to receive the first end and hold the first end in an adjustably fixed position;
  - a string mounting system adapted to receive the second end, the string mounting system comprising a spring assembly, said spring assembly comprising a spring that applies a tension to the second end of the string so as to hold the string at a perfect tune tension;
  - a force modulating member interposed between the second end of the string and the spring assembly, the force modulating member mounted so as to pivot about an axis, the spring assembly connected to the force modulating member so that the spring assembly applies a spring assembly force along a line of action that is a lever arm length from the axis;

wherein the force modulating member pivots as the second end of the musical string moves longitudinally over time due to string elongation or contraction, and as the force modulation member pivots, the spring assembly force changes and simultaneously the lever arm length changes, and wherein the change of lever arm length

25

counteracts the change of spring assembly force so that the resulting string tension remains within a desired range defined about the perfect tune tension.

2. A stringed musical instrument as in claim 1, wherein the desired range is within about 90% of the perfect tune tension, and wherein the string mounting system is adapted so that the spring maintains the string tension within the desired range when the second end moves longitudinally less than about 5% of the total string length.

3. A stringed musical instrument as in claim 2, wherein the perfect tune tension is between about 5 pounds and 200 pounds.

4. A stringed musical instrument as in claim 1, wherein the desired range is within about 98% of the perfect tune tension when the string elongates or contracts less than about 5% of the total string length.

5. A stringed musical instrument as in claim 1, wherein the desired range is within about 99% of the perfect tune tension when the string elongates or contracts less than about 5% of the total string length.

6. A stringed musical instrument as in claim 1, wherein the desired range is within about 99.5% of the perfect tune tension when the string elongates or contracts less than about 5% of the total string length.

7. A stringed musical instrument as in claim 1 additionally comprising a roller bridge disposed forwardly of the string mounting system, the roller bridge comprising a roller and an axle, the roller being adapted to support the string and rotate about the axle, wherein a ratio of a diameter of the roller to a diameter of the axle is greater than about 20.

8. A stringed musical instrument as in claim 1, wherein the spring assembly is configured to provide substantially the entire tension load in the string.

9. A stringed musical instrument as in claim 8, wherein the spring assembly comprises a single spring.

10. A stringed musical instrument as in claim 8, wherein the spring assembly comprises a plurality of springs.

11. A stringed musical instrument, comprising:

a musical string having first and second ends;

a first receiver adapted to receive the first end and hold the first end in an adjustably fixed position;

a string mounting system adapted to receive the second end, the string mounting system comprising a spring assembly, said spring assembly comprising a spring that applies a tension to the second end of the string so as to hold the string at a perfect tune tension;

a force modulating member interposed between the second end of the string and the spring assembly, the force modulating member mounted so as to pivot about an axis, the string and spring assembly each attached to the force modulating member so that the spring assembly has a mechanical advantage or disadvantage relative to the string;

wherein the force modulating member pivots as the second end of the musical string moves longitudinally over time due to string elongation or contraction, and such pivoting of the force modulating member changes the mechanical advantage or disadvantage of the spring assembly relative to the string so that the string tension remains within a desired range defined about the perfect tune tension; and

wherein the string mounting system comprises a stop configured to prevent rotation of the force modulation member in a rotational direction beyond a defined position.

12. A stringed musical instrument as in claim 11, wherein the force modulating member pivots within a range of about 10 degrees of rotation.

26

13. A stringed musical instrument as in claim 11, wherein the string mounting system comprises a sensor adapted to detect when the stop is engaged to prevent rotation and to generate a signal upon detection of such engagement.

14. A stringed musical instrument, comprising:

a musical string having first and second ends;

a first receiver adapted to receive the first end and hold the first end in an adjustably fixed position;

a string mounting system adapted to receive the second end, the string mounting system comprising a spring assembly that applies a tension to the second end of the string so as to hold the string at a perfect tune tension, the spring assembly being configured to provide substantially the entire tension load in the string; and

a force modulating member interposed between the second end of the string and the spring assembly, the string and spring assembly each attached to the force modulating member so that the spring assembly has a mechanical advantage or disadvantage relative to the string;

wherein the spring assembly comprises a first spring and a second spring, the first spring adapted to support a greater magnitude of tension in the string than the second spring, the second spring connected to the string through the string mounting system so that the mechanical advantage or disadvantage of the second spring relative to the string can be adjusted.

15. A stringed musical instrument, comprising:

a musical string;

a spring; and

a mechanical interface interposed between the string and the spring, the mechanical interface communicating force from the spring to the string so that the spring provides substantially all of the tension in the musical string;

wherein the mechanical interface comprises means for modifying the force exerted by the spring so that a magnitude of tension in the musical string differs from a magnitude of force exerted by the spring, and so that as the string elongates or contracts, the magnitude of tension in the musical string remains substantially constant despite substantial changes in the magnitude of force exerted by the spring.

16. A stringed musical instrument as in claim 15, wherein the means for modifying is configured so that a percent change in the force exerted by the spring corresponds to a percent change in the tension in the string, and the magnitude of the percent change in the tension in the string is less than the magnitude of the percent change in the force exerted by the spring.

17. A stringed musical instrument as in claim 16, wherein the means for modifying is adapted so that the magnitude of the change in tension applied to the string is not linearly related to the corresponding magnitude of the change in force exerted by the spring.

18. A stringed musical instrument as in claim 16, wherein the means for modifying comprises a means for variably interfacing a rotating part to the string by a camming action.

19. A stringed musical instrument as in claim 18, wherein the means for variably interfacing a rotating part to the string by a camming action comprises a string receiver.

20. A stringed musical instrument as in claim 16, wherein the mechanical interface connects to the spring and the string so that the spring force acts with a mechanical advantage or disadvantage relative to the string.

21. A stringed musical instrument as in claim 20, wherein the means for modifying is configured so that as the magni-

27

tude of spring force increases, the mechanical advantage of the spring with relation to the string decreases.

22. A stringed musical instrument as in claim 21, wherein the mechanical interface comprises a cam having a string receiver.

23. A stringed musical instrument as in claim 22, wherein the string receiver has a constant radius.

24. A stringed musical instrument as in claim 22, wherein the string receiver has a varying cam radius.

25. A stringed instrument as in claim 15, wherein the mechanical interface comprises a spiral-tracked conical pulley, and the musical string is supported in the track.

26. A stringed musical instrument, comprising:

a musical string having first and second

ends;

a first receiver adapted to hold the first end;

a string mounting system adapted to hold the second end and apply tension to the musical string, the string mounting system comprising a body, an arm and a spring, the spring operating between the arm and the body, the arm being movable relative to the body and communicating force from the spring to the second end of the musical string, the spring mounted so as to have a mechanical advantage or disadvantage relative to the arm, and the string mounting system configured so that substantially all of the tension applied to the string through the second end is provided by the spring;

wherein the arm is configured so that as the length of the string changes, the arm moves relative to the body, and

28

such arm movement causes the length of the spring to change and simultaneously causes the mechanical advantage or disadvantage of the spring relative to the arm to change; and

wherein the string mounting system is configured so that the changing spring length and changing mechanical advantage or disadvantage cooperate so that the tension applied to the string remains generally constant as the string length changes.

27. A stringed musical instrument as in claim 26, wherein the arm is movable relative to the body about a pivot, and the spring is attached to the body and to the arm so that a line of action of the spring is offset a lever arm distance from the pivot.

28. A stringed musical instrument as in claim 27, wherein the change in mechanical advantage of the spring relative to the arm as the string changes length comprises a change in the lever arm distance as the arm rotates about the pivot.

29. A stringed musical instrument as in claim 28, wherein the spring is attached to the body at a location that is selectively movable relative to the body, and wherein the lever arm distance can be adjusted by selectively moving the spring attachment location relative to the body.

30. A stringed musical instrument as in claim 29, wherein the body comprises a threaded rotatable mount member having a threaded shuttle thereon and configured so that rotating the mount member moves the shuttle linearly, and the spring attachment location is disposed on the shuttle.

\* \* \* \* \*